

BATKO

Made for Toshiba



FB-2008

Outdoor insulated housings
for PoE cameras

A proven, insulated, hermetically sealed housing required no heater nor blower.

This design has been tested since 1987 in severe Canadian subzero outdoor conditions, this rustproof, tamperproof, weatherproof, all aluminum, mineral fiber board insulated housing doesn't need a heater (nor a blower) to keep the camera in good working order. Lightweight, even if it is double-walled, this sealed housing includes a sealed connector to run in the cable. The front cover, that opens and extends horizontally for total camera access, is locked by 2 screws. The window comes with a 3/16" polycarbonate. It can be installed on any wall, ceiling or corner with the appropriate mounting bracket: FSM2012 for wall, FSP2012 for ceiling, FSC2012 for corner and FSA2012 for pole.

Fabrication

Body : All aluminum, 11 Ga. , #3003-H14 alloy
Window : 3/16" clear polycarbonate
Cover : Sliding, sealed, locked by 2 screws
Finish : White polyurethane coating
Weight : 6 lb (2.7 kg)

External Dimensions

Models : FB-2008
Height : 6.75" (171mm)
Width : 6.75" (171mm)
Length : 13.00" (330mm)

Internal Dimensions

Height : 4.0" (102mm)
Width : 3.75" (95mm)
Length : 8.0 " (203mm)
Camera (max) : 8.0" (203mm)

Accessories

FSM2012: Wall mount for FB-2008
FSP2012: Ceiling mount for FB-2008
FSC2012: Corner adaptor for FSM2012
FSA2012: Pole adaptor for FSM2012

No heater and blower required. The FB-2008 is completely insulated with mineral fiber board

