



ESV16U/32U

Embedded Network Video Recorder

High Performance, Cost-Effective NVR

With support for up to 16 and 32 IP cameras, the ESV16U/32U is a high performance, cost-effective network video recorder. The 4 removable hard drives (not included) allows for a total of 12TB of storage for maximum days of recording. 1U rack mount size optimizes space and maximizes storage density in a server grade chassis.

- Local viewing via VGA
- Up to 16 and 32 IP cameras
- Built-in Analytics, via VMS, on 16 channels
 - Object loss
 - Tripwire
 - Tamper detection
- Search functions
 - Event search
 - Time date search
 - Drill down graphic search
- Hard drive redundancy
 - Configurable RAID 0/1/5
- 1U space saving rack size
- Customizable Google & eMap
- eSATA output for extended storage
- iPhone/iPad app support
 - Live view
 - Playback
 - Audio
 - Snapshots
- Browser functions
 - Configure
 - Live viewing
 - Playback/search
 - Archiving
- Free VMS included (CMS Basic only)
 - Up to 16 recorders
- DHCP server
 - Automatically IP address cameras

ESV16U/32U

Embedded Network Video Recorder

TOSHIBA
Leading Innovation >>>

Model	ESV16U IP Recorder	ESV32U IP Recorder
OVERVIEW		
Max Number of Channels	16	32
IP Video Channels	16	32
Local Display	1 VGA	1 VGA
IP Compressions Supported	H.264, MPEG4, MJPEG	H.264, MPEG4, MJPEG
Max Camera Resolution	5 MP	5 MP
Number of Streams per Camera	2	2
STORAGE		
Storage Capacity	12TB (3TB HDD, Not Incl.)	12TB (3TB HDD, Not Incl.)
Number of HDDs	4 Removeable SATA	4 Removeable SATA
RAID	RAID 0, 1, 5, 10	RAID 0, 1, 5, 10
External Storage	eSATA x 1 (8TB max, 2TB HDD x 4)	eSATA x 1 (8TB max, 2TB HDD x 4)
Export Formats	AVI, MJPEG	AVI, MJPEG
DISPLAY		
Live View	(web) 1/4/16 (local) 1/4	(web) 1/4/16 (local) 1/4
INPUTS/OUTPUTS		
Audio Inputs	1 Line in, 1 MIC in, Up to 16 ^{*1}	1 Line in, 1 MIC in, Up to 32 ^{*1}
Audio Outputs	1 Line out	1 Line out
Sensor/Alarm Inputs	8	8
Alarm Outputs	4	4
USB	4 x USB 2.0	4 x USB 2.0
Ethernet	1 Gigabit Ethernet	1 Gigabit Ethernet
REMOTE CLIENTS INCLUDED		
Browser Client	Internet Explorer	Internet Explorer
Smartphone Apps	iPhone/Android	iPhone/Android
Tablet Apps	iPad/Android	iPad/Android
VMS Software	CMS Basic	CMS Basic
OTHER		
Operating System	Embedded Linux	Embedded Linux
ONVIF	Version 1.02	Version 1.02
User Interface	Mouse and Keyboard	Mouse and Keyboard
DIMENSIONS		
Dimension (H x W x D)	2.13" x 18.19" x 16.93"	2.13" x 18.19" x 16.93"
Weight	15.4 lbs	15.4 lbs
Rack Size	1U	1U
ENVIRONMENT		
Temperature	Operating: 32° to 104°F	Operating: 32° to 104°F
Humidity	Up to 80% R.H.	Up to 80% R.H.
POWER		
Power Input	AC100 - 240 V - 50/60Hz	AC100 - 240 V - 50/60Hz
Power Consumption	200W	200W
WARRANTY		
Limited Warranty	2 years	2 years

*1 on supported cameras



©2014 Toshiba America Information Systems, Inc. All rights reserved. All products and names mentioned are the property of their respective owners. While Toshiba has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice.

Toshiba America Information Systems, Inc.
Surveillance & IP Video Products, Imaging Systems Division
9740 Irvine Boulevard, Irvine, California 92618
1-877-855-1349 • www.toshibasecurity.com