

TOSHIBA

Leading Innovation >>>

IK-WR12A

IP NETWORK MEGAPIXEL DOME WITH
EXTREME LOW LIGHT CAPABILITIES



- IP66 rated weatherproof for outdoor with built-in heater/blower (-22° F to 122° F)
- IR LEDs provide 0.0 lux min. illumination
- IR LEDs enables video capture in total darkness for true 24/7 surveillance
- Vandal-resistant housing protects camera against tampering and damage
- 2MP resolution (1600 x 1200)
- Vari-focal 3-9 mm with 4x digital zoom
- Quad streaming MPEG4 and Motion JPEG
- Two-way audio
- Power over Ethernet, 12V DC or 24V AC
- Day/night imaging
- SD/SDHC card slot for local recording
- Privacy mask

IK-WR12A

IP NETWORK MEGAPIXEL DOME

IMAGING

Image Sensor	1/3.2-inch CMOS
Effective Picture Element	1600 x 1200
Scanning System	Progressive
Lens	Vari-Focal f=3mm to 9mm
Angle of view	H: 30° to 87° , V: 22° to 64°
Focus system	Manual
Image Compression Format	JPEG, MPEG4 (dual codec)
Minimum illumination	0.0 lux/F1.2 with IR LED on
White Balance	AWB
Gain AGC	Auto
BLC	Yes
Flickerless	Yes, 50Hz/60Hz selectable
Privacy Mask	Yes
Tamper Detection	Yes
Motion Detection	Yes
ePTZ	Yes
Zoom	3X optical, 4x digital
Day/night	Removable IR-cut filter

ENVIRONMENT

IP Code	IP66
Heater/Fan (Blower)	Built in
Temperature range	-22° F to 122° F (-30° C to 50° C)

NETWORKING

Support-protocol	TCP/ IP, HTTP, HTTPs, UPnP, SNMP RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE
Internet protocol	IPv4, IPv6
Camera Setup Program	Installation Wizard ActiveX
MPEG4/JPEG	Simultaneous four streamings
Band width control	QoS, CoS
Image Sizes	1600x1200, 1280x960, 800x600, 640x480, 320x240, 176 x144
Frames per second (fps)	SVGA: 30 fps (MPEG, JPEG) UXGA: 15 fps (MPEG), 15 fps (JPEG)
Security	Multi level ID/Password, IP address filtering, HTTPS, 802.1x port-based authentication
DDNS	no-ip.com changelP.com
Audio I/O	MIC IN / LINE OUT 2-way audio (SIP)
Multi-cast/Uni-cast	Yes
Alarm recording	Yes
Recording in client PC	Yes
Recording to SD Card	Yes (SD, SDHC)
Export/upload function	Yes
E-mail, FTP	Yes
Daylight savings	Yes

INTERFACE

Ethernet Connectors	10 Base-T/100 Base-Tx RJ-45
Audio in/out terminal	Yes (Mic In / Line out)
Web browser	Internet Explorer® V8.0 or later
Operating System	MS Windows® XP, Vista, 7



The IK-WR12A is weatherproof and vandal-resistant. It has an IP66 rating, meaning that its electronics are protected against dust, water/moisture/humidity, and impact. It will also detect tampering by blockage or spray paint. Install it with confidence in high-risk schools, jails, retail, parking lots, warehouses, airports, or anywhere outdoors. The advanced codec technology allows you to easily view, control, and manage all networked cameras using a standard web browser or Toshiba's surveillance management software from any networked computer.

MECHANICAL

Dimensions	6.8" (ø) x 5.3" (H)
IR Illuminators	Effective up to 20 meters
Humidity of operation	20 to 90%
Weight	4.81 lbs (2,184 g)
Power Requirements	DC 12V±10%, AC 24V±10%, PoE
Power Consumption	7.2W (12VDC), 14.4W (24VAC)
ROHS	Compliant
Standards	FCC/A and B, IC (ICES-003), UL60950, CSA C22.2

OPTIONAL ACCESSORIES

JK-PHO12	Outdoor Housing
JK-PMA12	Pole Mount Adapter
JK-CMA12	Corner Mount adapter
JK-PMH12	Pendant Mount Head
JK-WM12	Wall Mount
JK-PMP12	Pendant Mount Pipe

INCLUDED ACCESSORIES AC adaptor, Bottom base, User's manual and install software (CD-ROM), Quick Start guide & Important Safeguards, Warranty, Alignment Sticker, Ceiling hole template sticker, Hex Key Wrench, RJ45 Female/Female Coupler, Silica Gel, Screws (x7), Anchors (x4)